



Holiday OWL

FP-285



A member of the OWL family

Holiday OWL	FP-284
PoE OWL	FP-287
AC to DC OWL	FP-288
Step-Down OWL	FP-289

Timed and Switched Auxiliary Power for Holiday Lights



Specifications:

Input Voltage: 105 – 130 VAC

Output Voltage: 120 VAC
Standard Electrical Outlet

Turn-on: Sunset

Turn-off: 6 Hours after Sunset

Housing: UV Stabilized, Impact Resistant,
Gray Polycarbonate

ANSI Standard: Conforms to ANSI C136.10
and Proposed ANSI C136.35

Temperature Rating: -40 to +70C

Ordering Information:

Model # FP284 – Consult Factory

The Holiday OWL provides timed and switched power for decorative holiday lights. The receptacle is energized at sunset and de-energized 6 hours later. Normal dusk to dawn photoelectric operation of the streetlight is maintained.

Applications Include:

- Christmas Lights
- Special Event Lights

About FP Outdoor Lighting Controls

For more than 60 years FP OLC has been the largest global provider of photoelectric roadway lighting controls for the electric power industry. Our auxiliary power devices are universally accepted at conservative electric utilities and are the product of choice for streetlight mounted equipment manufacturers.

FP OLC is ready to help you power your future.